

General Specifications for Waterfall Systems Water Softeners

Models: Autotrol - (AA, AL, AL-LX), Fleck & Clack - (AM, AM-SXT, AM-SXT58, AM-EC)

Est. # of People in Home	Mineral Tank Size	Grain Capacity*	Cubic Feet of Resin - LBS	Backwash Flow Rate*	Service Flow Rate*	Gallons Per Regeneration*	Salt Usage - LBS Per Regeneration*	Brine Tank Size
1	8" X 35"	10K to 16K	.5 - 26LBS	1.2 GPM	6.0	26 to 50	3 to 8	18" X 33"
1 - 2	8" X 40"	15K to 24K	.75 - 39LBS	1.5 GPM	7.0	34 to 62	4.5 to 12	18" X 33"
1 - 3	10" X 40"	20K to 32K	1.0 - 52LBS	2.0 GPM	10.0	45 to 82	6 to 16	18" X 33"
1 - 4	10" X 54"	30K to 48K	1.5 - 78LBS	2.4 GPM	12.0	58 to 100	9 to 24	18" X 33"
2 - 5	12" X 48"	40K to 64K	2.0 - 104LBS	3.5 GPM	15.0	81 to 145	12 to 32	18" X 40"

*The information provided above including grain capacity, water usage, flow rates and salt usage can vary depending on the softener size and condition of water.